

Model 5100 HD Gas Analyzer for Measuring Oxygen in Process Gas

Based on Tunable Diode Laser Absorption Spectroscopy (TDLAS)

The Model 5100 HD offers high specificity, sensitivity and extremely fast response speeds.



Features and Benefits

- || **Noncontact Measurement**
Noncontact measurement offers low maintenance
- || **All Digital Signal Processing**
32-bit microcontroller capable of sophisticated signal processing
- || **Web-Based Interface**
To monitor the analyzer remotely, all you need is the IP address of the analyzer
- || **Connectivity**
Modbus, Ethernet, dry contacts and analog outputs
- || **Real-Time Performance Monitoring**
Laser line-lock verification using internal reference cell
- || **NEMA 4X Enclosure houses the electronic components**
Designed for outdoor installation
- || **Fully-Integrated Sample Handling**
Standard feature
- || **Resistant to Contamination**
No interference from gas phase amines, glycol, methanol, H₂S and mercaptans
- || **Hazardous Area Options for Model 5100 HD**
Class I Div 1, BCD T3; Ex De IIB+H2 T3 Gb; Pressurized Class 1 Zone 1 ATEX de IIB+H2 T3 (or T5);
Div 2 and Zone 2 are also available.
INMETRO Certification for Zone 2 -
Ex nA nC ic op is IIC T3 Gb

Model 5100 HD Gas Analyzer

Specifications

Typical Operating Range:

0-1% Min / 0-30% Max. Other ranges available subject to application. Consult AMETEK.

Accuracy: 1% full scale range or ± 1000 ppm or whichever is higher

Repeatability: 1% of full scale range or ± 300 ppm or whichever is higher

Environment:

Ambient Temperature: -20°C to +50°C (-4°F to 122°F)

Electrical Classification:

Class I Div 1, BCD T3; Ex De IIB+H2 T3 Gb; Pressurized Class 1 Zone 1 ATEX de IIB+H2 T3 (or T5); Div 2 and Zone 2 are also available. INMETRO Certification for Zone 2 - Ex nA nC ic op is IIC T3 Gb

Relative Humidity: 0% to 90%, non-condensing

Sample Flow Rate: 1 to 10 SLPM recommended (2 - 20 SCFH)

Sample Cell Pressure: 70 to 170 kPa absolute (10-25 psia)

Speed of Response: < 1 second photometric response. Total system response is dependent on sample flowrate.

Outputs: 4-line x 20-character alphanumeric VF display.

Fast Ethernet (IEEE802.3)

RS-485 serial port, isolated (supports Modicon Modbus RTU)

(1) isolated 4-20 mA loop-powered analog output

(4) dry relay contacts. Contact rating 30 VAC, 60 VDC, 100 VA resistive

Electrical Requirements:

120 VAC (108-132V); 47-63 Hz, or 240 VAC (216-264V), 47-63 Hz 24 VDC (no oven heater available)

Power Requirements:

450W with optional heater

Physical Dimensions (HxWxD):

64.23 cm x 83.03 cm x 29.53 cm (25.29" x 32.69" x 11.63")

Weight:

58.97 Kg (130 lb)

Enclosure: IP-65, NEMA 4X



150 Freeport Road, Pittsburgh, PA 15238
Ph. +1-412-828-9040, Fax +1-422-826-0399
www.ametekpi.com



© 2015, by AMETEK, Inc.
All rights reserved. Printed in the U.S.A.
F-0113 Rev. 8 (0115)

One of a family of innovative process analyzer solutions from AMETEK Process Instruments.
Specifications subject to change without notice.

SALES, SERVICE AND MANUFACTURING:

USA - Pennsylvania
150 Freeport Road, Pittsburgh PA 15238 • Tel: +1-412-828-9040, Fax: +1-412-826-0399

USA - Delaware
455 Corporate Blvd., Newark DE 19702 • Tel: +1-302-456-4400, Fax: +1-302-456-4444

Canada - Alberta
2876 Sunridge Way N.E., Calgary AB T1Y 7H2 • Tel: +1-403-235-8400, Fax: +1-403-248-3550

WORLDWIDE SALES AND SERVICE LOCATIONS:

USA - Houston, Texas
Tel: +1-713-466-4900, Fax: +1-713-849-1924

BRAZIL
Tel: +55 19 2107 4100

CHINA
Beijing / Tel: +86 10 8526 2111, Fax: +86 10 8526 2141
Chengdu / Tel: +86 28 8675 8111, Fax: +86 28-8675 8141
Shanghai / Tel: +86 21 6426 8111, Fax: +86 21 6426 7818

USA - Austin, Texas
Tel: +1-512-252-2440, Fax: +1-515-252-2430

FRANCE
Tel: +33 1 30 68 89 20, Fax: +33 1 30 68 89 99

GERMANY
Tel: +49 21 59 91 36 0, Fax: +49 21 59 91 3639

INDIA
Tel: +91 80 6782 3200, Fax: +91 80 6782 3232

SINGAPORE
Tel: +65 6484 2388, Fax: +65 6481 6588

TDLAS